

SAFETY DATA SHEET
DIADEM FLOOR POLISH STRIPPER

Page: 1

Compilation date: 25/05/2016

Revision date: 30/08/2018

Revision No: 9

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: DIADEM FLOOR POLISH STRIPPER

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Floor cleaner for professional use.

1.3. Details of the supplier of the safety data sheet

Company name: North Lancs Disposables

Unit 1

Burrow Rural Workshops

Woodman Lane

Burrow

Carnforth

LA6 2RL

Tel: 08446 933 257

Fax: 08446 933 256

Email: mail@northlancsdisposables.com

1.4. Emergency telephone number

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Skin Corr. 1B: H314

Most important adverse effects: Causes severe skin burns and eye damage.

2.2. Label elements

Label elements:

Hazard statements: H314: Causes severe skin burns and eye damage.

Hazard pictograms: GHS05: Corrosion



Signal words: Danger

Precautionary statements: P260: Do not breathe dust/fumes/gas/mist/vapours/spray.

P280: Wear protective gloves/eye protection.

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.

[cont...]

SAFETY DATA SHEET
DIADEM FLOOR POLISH STRIPPER

Page: 2

Rinse skin with water .

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

SODIUM METASILICATE PENTAHYDRATE - REACH registered number(s): 01-2119449811-37

EINECS	CAS	PBT / WEL	CLP Classification	Percent
229-912-9	10213-79-3	-	Met. Corr. 1: H290; Skin Corr. 1B: H314; STOT SE 3: H335	1-10%

ALCOHOLS, C9-11, BRANCHED AND LINEAR, ETHOXYLATED, SULFATES, SODIUM SALTS

500-465-4	160901-28-0	-	Eye Dam. 1: H318; Skin Irrit. 2: H315	1-10%
-----------	-------------	---	---------------------------------------	-------

2-AMINOETHANOL - REACH registered number(s): 01-2119486455-28

205-483-3	141-43-5	-	Acute Tox. 4: H332; Acute Tox. 4: H312; Acute Tox. 4: H302; Skin Corr. 1B: H314	1-10%
-----------	----------	---	---	-------

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin.

Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Transfer to hospital if there are burns or symptoms of poisoning.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

Ingestion: Wash out mouth with water. Do not induce vomiting. Give 1 cup of water to drink every 10 minutes. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. Transfer to hospital as soon as possible.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious and breathing is OK, place in the recovery position. If conscious, ensure the casualty sits or lies down. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Transfer to hospital as soon as possible.

[cont...]

SAFETY DATA SHEET
DIADEM FLOOR POLISH STRIPPER

Page: 3

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: Blistering may occur. Progressive ulceration will occur if treatment is not immediate.

Eye contact: Corneal burns may occur. May cause permanent damage.

Ingestion: Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.

Inhalation: There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Corrosive. In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Notify the police and fire brigade immediately. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

[cont...]

SAFETY DATA SHEET
 DIADEM FLOOR POLISH STRIPPER

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.
 Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.
Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

2-AMINOETHANOL

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	2.5 mg/m ³	7.6 mg/m ³	-	-

DNEL/PNEC Values

Hazardous ingredients:

SODIUM METASILICATE PENTAHYDRATE

Type	Exposure	Value	Population	Effect
DNEL	Dermal	1.49	Workers	Systemic
DNEL	Inhalation	6.22	Workers	Systemic
DNEL	Dermal	0.74	Consumers	Systemic
DNEL	Inhalation	1.55	Consumers	Systemic
DNEL	Oral	0.74	Consumers	Systemic
PNEC	Fresh water	7.5	-	-
PNEC	Marine water	1	-	-
PNEC	Microorganisms in sewage treatment	1000	-	-

2-AMINOETHANOL

Type	Exposure	Value	Population	Effect
DNEL	Dermal	1	Workers	Systemic

SAFETY DATA SHEET
 DIADEM FLOOR POLISH STRIPPER

Page: 5

DNEL	Inhalation	3.3	Workers	Systemic
DNEL	Inhalation	3.3	Workers	Local
DNEL	Dermal	0.24	Consumers	Systemic
DNEL	Inhalation	2	Consumers	Systemic
DNEL	Inhalation	2	Consumers	Local
DNEL	Oral	3.75	Consumers	Systemic
PNEC	Fresh water	0.085	-	-
PNEC	Marine water	0.0085	-	-
PNEC	Fresh water sediments	0.425	-	-
PNEC	Marine sediments	0.0425	-	-
PNEC	Soil (agricultural)	0.035	-	-
PNEC	Microorganisms in sewage treatment	100	-	-

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Impermeable gloves.

Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Red

Odour: Characteristic odour

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Soluble

Also soluble in: Most organic solvents.

Viscosity: Non-viscous

Flash point°C: >70

pH: >11.5

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

[cont...]

SAFETY DATA SHEET
DIADEM FLOOR POLISH STRIPPER

Page: 6

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

ALCOHOLS, C9-11, BRANCHED AND LINEAR, ETHOXYLATED, SULFATES, SODIUM SALTS

DERMAL	RAT	LD50	>2000	mg/kg
ORL	RAT	LD50	>2000	mg/kg

2-AMINOETHANOL

DERMAL	RBT	LD50	1,025.0	mg/kg
DUST/MIST	-	-	1.5	mg/l
GASES	-	-	4,500.0	ppmV
ORAL	RAT	LD50	1,720.0	mg/kg
VAPOURS	-	-	11.0	mg/l

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: Blistering may occur. Progressive ulceration will occur if treatment is not immediate.

Eye contact: Corneal burns may occur. May cause permanent damage.

Ingestion: Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.

Inhalation: There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

[cont...]

SAFETY DATA SHEET
DIADEM FLOOR POLISH STRIPPER

Page: 7

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

SODIUM METASILICATE PENTAHYDRATE

Daphnia magna	48H EC50	1700	mg/l
Scenedesmus Subspicatus	72H ErC50	207	mg/l
ZEBRAFISH (Brachydanio rerio)	96H LC50	210	mg/l

ALCOHOLS, C9-11, BRANCHED AND LINEAR, ETHOXYLATED, SULFATES, SODIUM SALTS

ALGAE	48H EC50	31.3	mg/l
DAPHNIA	48H EC50	91	mg/l
FISH	96H LC50	7.1	mg/l

2-AMINOETHANOL

BLUEGILL (Lepomis macrochirus)	96H ErC50	300 - 1000	mg/l
Daphnia magna	48H EC50	65	mg/l
Pseudokirchneriella subcapitata	72H ErC50	2.8	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H ErC50	114 - 196	mg/l
Scenedesmus Subspicatus	72H ErC50	22	mg/l
ZEBRAFISH (Brachydanio rerio)	96H ErC50	3684	mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

[cont...]

SAFETY DATA SHEET
DIADEM FLOOR POLISH STRIPPER

Page: 8

Section 14: Transport information

14.1. UN number

UN number: UN1760

14.2. UN proper shipping name

Shipping name: CORROSIVE LIQUID, N.O.S.
(DISODIUM METASILICATE)

14.3. Transport hazard class(es)

Transport class: 8

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H290: May be corrosive to metals.
H302: Harmful if swallowed.
H312: Harmful in contact with skin.
H314: Causes severe skin burns and eye damage.
H315: Causes skin irritation.
H318: Causes serious eye damage.
H332: Harmful if inhaled.
H335: May cause respiratory irritation.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

[cont...]

SAFETY DATA SHEET
DIADEM FLOOR POLISH STRIPPER

Page: 9

and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.