

1. Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: STRIPELINE MARKING PAINT ORANGE

Article number: LMOE

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: TYGRIS Industrial
Unit 31
Kyle Road Industrial Estate
Irvine
Ayrshire
KA12 8LE
Tel +44 (0) 1294 311 066
Fax +44 (0) 1294 277 115
Email technical@tygrisindustrial.com

Further information obtainable from: Technical Department

1.4 Emergency telephone number: Tel +44 (0) 1294 311 066

2. Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Flam. Aerosol 1: H222; Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Lact.: H362; STOT SE 3: H336; -: EUH066; -: EUH208; -: H229

Most important adverse effects: Repeated exposure may cause skin dryness or cracking. Contains isodecyloxypropylamine acetate. May produce an allergic reaction. Extremely flammable aerosol. Pressurised container: May burst if heated. Causes serious eye irritation. May cause drowsiness or dizziness. May cause harm to breast-fed children. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Hazard statements: EUH066: Repeated exposure may cause skin dryness or cracking.
EUH208: Contains isodecyloxypropylamine acetate. May produce an allergic reaction.
H222: Extremely flammable aerosol.
H229: Pressurised container: May burst if heated
H319: Causes serious eye irritation.
H336: May cause drowsiness or dizziness.
H362: May cause harm to breast-fed children.
H411: Toxic to aquatic life with long lasting effects.

Hazard pictograms: GHS02: Flame
GHS07: Exclamation mark
GHS09: Environmental



Signal word: Danger

Precautionary statements: P102: Keep out of reach of children.
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211: Do not spray on an open flame or other ignition source.
P251: Do not pierce or burn, even after use.
P260: Do not breathe dust/fumes/gas/mist/vapours/spray.
P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50°C.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

3. Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

ACETONE - REACH registered number(s): 01-2119471330-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
200-662-2	67-64-1	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	10-30%

SOLVENT NAPHTHA (PETROLEUM), LIGHT AROMATIC.; LOW BOILING POINT NAPHTHA

265-199-0	64742-95-6	-	Flam. Liq. 3: H226; Asp. Tox. 1: H304; STOT SE 3: H335; Aquatic Chronic 2: H411; STOT SE 3: H336; -: EUH066	1-10%
-----------	------------	---	---	-------

N-BUTYL ACETATE

204-658-1	123-86-4	-	Flam. Liq. 3: H226; STOT SE 3: H336; -: EUH066	1-10%
-----------	----------	---	--	-------

1,2,4-TRIMETHYLBENZENE

202-436-9	95-63-6	-	Flam. Liq. 3: H226; Acute Tox. 4: H332; Eye Irrit. 2: H319; STOT SE 3: H335; Skin Irrit. 2: H315; Aquatic Chronic 2: H411	1-10%
-----------	---------	---	---	-------

ISOBUTANE

200-857-2	75-28-5	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	1-10%
-----------	---------	--	-------------------------------------	-------

ALKANES, C14-17, CHLORO

287-477-0	85535-85-9	-	Lact.: H362; Aquatic Chronic 1: H410; Aquatic Acute 1: H400	1-10%
-----------	------------	---	---	-------

ETHYL ACETATE

205-500-4	141-78-6	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	1-10%
-----------	----------	---	--	-------

MESITYLENE

203-604-4	108-67-8	-	Flam. Liq. 3: H226; STOT SE 3: H335; Aquatic Chronic 2: H411	1-10%
-----------	----------	---	--	-------

ISODECYLOXPROPYLAMINE ACETATE

-	28701-67-9	-	Acute Tox. 4: H302; Skin Corr. 1B: H314; STOT SE 3: H335; Aquatic Chronic 1: H410; Skin Sens. 1: H317	<1%
---	------------	---	---	-----

4. First aid measures

4.1. Description of first aid measures

- Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin.
- Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.
- Ingestion:** Do not induce vomiting. Consult a doctor.
- Inhalation:** Move to fresh air in case of accidental inhalation of vapours.

4.2. Most important symptoms and effects, both acute and delayed

- Skin contact:** No data available.
- Eye contact:** No data available.
- Ingestion:** No data available.
- Inhalation:** No data available.
- Delayed / immediate effects:** No data available.

4.3. Indication of any immediate medical attention and special treatment needed

- Immediate / special treatment:** Not applicable.

5. Firefighting measures

5.1 Extinguishing media

- Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used.

5.2. Special hazards arising from the substance or mixture

- Exposure hazards:** Extremely flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.

5.3. Advice for fire-fighters

- Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Eliminate all sources of ignition. If outside do not approach from downwind.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Do not use equipment in clean-up procedure which may produce sparks. Clean-up should be dealt with only by qualified personnel familiar with the specific substance.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

7. Handling and storage

7.1 Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Smoking is forbidden. Use non-sparking tools.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. Keep away from direct sunlight. Keep away from sources of ignition.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

8. Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

ACETONE

Workplace exposure limits:

Respirable dust:

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	500ppm 1210mg/m ³	1500ppm 3620mg/m ³	-	-

N-BUTYL ACETATE

UK	724 mg/m ³	966 mg/m ³	-	-
----	-----------------------	-----------------------	---	---

1,2,4-TRIMETHYLBENZENE

UK	125 mg/m ³	-	-	-
----	-----------------------	---	---	---

ISOBUTANE

UK	2400 mg/m ³	9600 mg/m ³	-	-
----	------------------------	------------------------	---	---

ETHYL ACETATE

UK	200 ppm	400 ppm	-	-
----	---------	---------	---	---

MESITYLENE

UK	25 ppm	-	-	-
----	--------	---	---	---

DNEL/PNEC Values

Hazardous ingredients:

ACETONE

Type	Exposure	Value	Population	Effect
DNEL	Dermal	186mg/kg/day	Workers	Systemic
DNEL	Inhalation	2420mg/m ³	Workers	Local
DNEL	Inhalation	1210mg/m ³	Workers	Systemic
DNEL	Oral	62mg/kg/day	Consumers	Systemic
DNEL	Dermal	62mg/m ³	Consumers	Systemic
DNEL	Inhalation	200mg/m ³	Consumers	Systemic
PNEC	Fresh water	10.6mg/l	-	-
PNEC	Marine water	1.06mg/l	-	-
PNEC	Fresh water	Intermittent release	-	-
PNEC	Fresh water sediments	30.4 mg/kg	-	-
PNEC	Marine sediments	3.04mg/kg	-	-
PNEC	Soil (agricultural)	29.5mg/kg	-	-
PNEC	Microorganisms in sewage treatment	100mg/l	-	-

8.2. Exposure controls

Engineering measures:	Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.
Respiratory equipment:	Respiratory protection not required.
Hand protection:	Chemically resistant gloves.
Eye protection:	Safety glasses. Ensure eye bath is to hand.
Skin protection:	Protective clothing.
Environmental:	Prevent from entering in public sewers or the immediate environment.

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

State:	Aerosol
Colour:	Orange
Odour:	Characteristic odour
Flash point°C:	-60

9.2. Other information

Other information:	No data available.
---------------------------	--------------------

10. Stability and reactivity

10.1. Reactivity

Reactivity:	Stable under recommended transport or storage conditions.
--------------------	---

10.2. Chemical stability

Chemical stability:	Stable under normal conditions. Stable at room temperature.
----------------------------	---

10.3. Possibility of hazardous reactions

Hazardous reactions:	Hazardous reactions will not occur under normal transport or storage conditions.
-----------------------------	--

10.4. Conditions to avoid

Conditions to avoid:	Direct sunlight. Heat. Hot surfaces. Sources of ignition. Flames.
-----------------------------	---

10.5. Incompatible materials

Materials to avoid:	Strong oxidising agents. Strong acids.
----------------------------	--

10.6. Hazardous decomposition products

Haz. decomp. products:	In combustion emits toxic fumes.
-------------------------------	----------------------------------

11. Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

ACETONE

DERMAL	RAT	LD50	>7400	mg/kg
DERMAL	RBT	LD50	2000	mg/kg
ORAL	RAT	LD50	5800	mg/kg
VAPOURS	RAT	4H LC50	76000	mg/l

N-BUTYL ACETATE

ORL	MUS	LD50	6	gm/kg
ORL	RAT	LD50	10768	mg/kg

1,2,4-TRIMETHYLBENZENE

IPR	RAT	LDLO	1752	mg/kg
ORL	RAT	LD50	5	gm/kg

ETHYL ACETATE

ORL	MUS	LD50	4100	mg/kg
ORL	RAT	LD50	5620	mg/kg
SCU	RAT	LDLO	5	gm/kg

MESITYLENE

IPR	GPG	LDLO	1303	mg/kg
-----	-----	------	------	-------

Relevant hazards for product:

Hazard	Route	Basis
Serious eye damage/irritation	OPT	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Inhalation: No data available.

Delayed / immediate effects: No data available.

Other information: Not applicable.

12. Ecological information

12.1. Toxicity

Hazardous ingredients:

ACETONE

ALGAE	192H EC10	530	mg/l
Activated Sludge	30m EC10	1000	mg/l
DAPHNIA	48H EC50	8800	mg/l
Daphnia magna	192H EC10	2212	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	5540	mg/l

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms.

13. Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Recovery operations: Not applicable.

Disposal of packaging: Not applicable.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. Transport information

14.1. UN number

UN number: UN1950

14.2. UN proper shipping name

Shipping name: AEROSOLS

14.3. Transport hazard class(es)

Transport class: 2

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D

Transport category: 2

15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical safety assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

16. Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.
EUH208: Contains <name of sensitising substance>. May produce an allergic reaction.
H222: Extremely flammable aerosol.
H225: Highly flammable liquid and vapour.
H226: Flammable liquid and vapour.
H229: Pressurised container: May burst if heated
H302: Harmful if swallowed.
H304: May be fatal if swallowed and enters airways.
H314: Causes severe skin burns and eye damage.
H315: Causes skin irritation.
H317: May cause an allergic skin reaction.
H319: Causes serious eye irritation.
H332: Harmful if inhaled.
H335: May cause respiratory irritation.
H336: May cause drowsiness or dizziness.
H362: May cause harm to breast-fed children.
H410: Very toxic to aquatic life with long lasting effects.
H411: Toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

